


FEATURES

- Frosted area with fingerprint-free technology
- Special anti-corrosion Mirror treatment
- Suitable for Damp Location
- 5mm Environmental Copper free silver Mirror
- Easy installation
- Custom Mirror dimensions available

INSTALLATION







AVAILABLE OPTIONS

- Defogger
- Dimming 0-10V
- Touch Sensor
- Motion Sensor
- Magnifying Mirror X3 & X5
- LED Digital Clock
- Night Light
- Power Plug
- * See "Options" page for more information.

LIGHTING SPECIFICATIONS

- Easy replaceable LEDs
- CCT: 3000 | 4000 | 6000
- 427 Lumens per foot*
 - * Higher Lumen per foot available
- CRI: 80 +
- LED Life: Average 90,000 hrs.



Frosted area with Fingerprint-free technology





Special anti-corrosion Mirror treatment



5mm Environmental Copper free silver Mirror



Date: 04 March 2019

Page: 1/4

LUMITHREE

LM-1103 Lit Mirror

Product Specifications

ORDERING CODE

LM-1103-LED - - - - - - - -

Product ID	Dimensions	Voltage	ССТ	Diffuser	Installation	Mounting	Options
LM-1103-LED	21 x 30 - 21"W x 30"H 28 - 28" Dia 30 - 30" Dia 36 - 36" Dia C - Custom	120 - 120V 277 - 277V	30 - 3000k 40 - 4000k 60 - 6000k	FR - Frosted IF - Ice Frost C - Custom* *Consult factory	HR - Horizontal* VT - Vertical* *Oval Mirrors only HR VT	CM - Cleats Mounting* KM - Keyhole Mounting** *Frame White Powdercoated ** Frame Satin Aluminum	DF - Defogger DM - Dimming 0-10V TS - Touch Sensor MS- Motion Sensor M3 - Magnifying Mirror x3 M5 - Magnifying Mirror x5 LD - LED Digital Clock TNL - Top Night Light BNL - Bottom Night Light PP - Power Plug

LIGHTING SPECIFICATIONS

Standard Product: Hardwired

				Standard Froduct: Hardwired
Dimensions	Wattage	Lumen Output	CRI	
21" W x 30" H x 2" D (Oval Fixture) 28" Diameter x 2" D 30" Diameter x 2" D 36" Diameter x 2" D	24 Watt 26 Watt 28 Watt 35 Watt	2375 Total Lumen Output 2599 Total Lumen Output 2822 Total Lumen Output 3492 Total Lumen Output	80+ CRI 80+ CRI 80+ CRI 80+ CRI	→ Depth (D)
(H) Height (H) 2" Frost	ted Area		— Cutout for Connections (Center of the steel frame)	CM Frame White Powdercoated KM Frame Satin Aluminum

^{*} Not to Scale. Frosted area and border width may change depending on Mirror dimensions.

 APPROVED BY:
 SIGNATURE:
 DATE:

 File: LM - 1103 - SPEC - REV2
 Date: 04 March 2019
 Page: 2/4






LUMITHREE

LM-1103 Lit Mirror

Product Specifications

MOUNTING

CM - Cleat Mounting




Back View	Mirror
-----------	--------

Front View Frame

21" W x 30" H x 2" D (Oval Fixture)	W = 11.60''	H = 20.60''
28" Diameter x 2" D	W = 18.60''	H = 18.60''
30" Diameter x 2" D	W = 20.60''	H = 20.60''
36" Diameter x 2" D	W = 26.60''	H = 26.60''

KM - Keyhole Mounting



Back View Mirror

21" W x 30" H x 2" D (Oval Fixture)	Template will be provided
28" Diameter x 2" D	Template will be provided
30" Diameter x 2" D	Template will be provided
36" Diameter x 2" D	Template will be provided

DIFFUSER



FROSTED



ICE FROST

Frosted area with fingerprint-free technology Special anti-corrosion Mirror treatment 5mm Environmental Copper free silver Mirror

File: LM - 1103 - SPEC - REV2 Date: 04 March 2019 Page: 3/4





LUMITHREE

LM-1103 Lit Mirror

Product Specifications | Options

















DF - Defogger

Electrical defogger heated pad system will help you remove the steam from the Mirror.

DM - Dimming

0-10V dimming available on all our mirrors.

TS - Touch Sensor

Innovative and attractive touch sensor with an LED night light.

MS- Motion Sensor

Placed on the side or bottom, simply wave your hands to turn on or off.

M3 - Magnifying Mirror x3 / **M5** - Magnifying Mirror x5 3X or 5X magnifying mirror with an LED ring around.

LD - LED Digital Clock

Screen with an LED clock.

NL - Night Light

Night light available for top, bottom or both.

PP - Power Plug

Power Plug available on all Mirrors, and can be located in any desired location.

File: LM - 1103 - SPEC - REV2

Date: 04 March 2019

Page: 4/4

